

Paediatric Wheelchair Solutions Chart

	FLEXX JUNIOR	LITTLE WAVE CLIK	ROGUE XP	LITTLE WAVE FLIP	LITTLE WAVE ARC	FOCUS CR	KIDEVO MINI TILT	KIDEVO PRIME TILT
DESCRIPTION	Fully adjustable folding frame paediatric wheelchair	Ultra lightweight, paediatric fixed frame wheelchair. Highly adjustable and configurable. Click based, simple depth growth system. Width growth kit available on request.	Ultra lightweight, fixed frame wheelchair. Highly adjustable and configurable to maximise independence. Simple depth growth system built-in, width growth kit available on request.	Folding frame, paediatric tilt-in-space wheelchair. Highly adjustable and configurable. Simple depth growth system built-in, width growth kit available on request.	Ultra-lightweight with 45 degree effortless, tilt-in-space mechanism. Configurable with adjustable depth growth built in. Width growth kit available on request. Lightest folding pivot tilt option available.	50 Degree Tilt-in-space with a centre of gravity system that has a single rotation point. Highly adjustable and configurable.	Highly customisable seating and adjustable features to grow with the child. Offers Tilt-in-space and ideal for self-propelling.	Highly customisable seating and adjustable features to grow with the child. Offers Tilt-in-space, ideal for self-propelling and designed with older children in mind.
TYPE	Self-propelling or Transit	Self-propelling	Self-propelling	Transit with Tilt-in-space	Transit with Tilt-in-space	Transit with Tilt-in-space	Self-propelling with Tilt-in-space	Self-propelling with Tilt-in-space
SEAT WIDTH RANGE	10" - 14"	8" - 16"	10" - 18"	10" - 18"	10" - 18"	14" - 24"	6" - 13"	10" - 20"
SEAT DEPTH RANGE	11" - 15"	8" - 16"	10" - 20"	12" - 20"	12" - 20"	14" - 22"	6" - 14"	8" - 20"
FOLDING	Yes	No	No	Yes	Yes	No	No	No
TILT 'N' SPACE	No	No	No	Yes (hand or foot options) 0° to 45°	Yes (hand or foot options) 0° to 45°	Yes, -5° to 50°	-5° to 40°	-10° to 50°
RECLINE RANGE	Fixed -4° to + 16°	Fixed -10° to + 10°	Fixed -10° to + 10°	Optional	Optional	-5° to + 50°	-5° to 40°	-10° to 50°
MIN. SEAT-TO-FLOOR HEIGHT	15.5"	11.5"	11.5"	13"	14.5"	13.5"	35.5cm with a 20" drive wheel	47cm with a 22" drive wheel
ADJUSTABLE HEIGHT PUSHCANES	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
GROWTH KIT INCLUDED	Built-in (Depth Only)	Yes	Yes	Yes	Yes	Yes	Built-in	Built-in
STANDARD BRAKE	Push to lock with brake extension handles	Push to Lock	Push to Lock	Push or Pull to Lock and Attendant. Optional Drum Brake	Push or Pull to Lock and Attendant. Optional Drum Brake	Push to lock	Drum Brake or Combi-Drum Brake	Drum Brake or Combi-Drum Brake
USER WEIGHT LIMIT	75 kg	75 kg	90 kg	75 kg	75 kg	136kg (181 kg HD option)	50 kg	75 kg
STANDARD FEATURES	Height adjustable flip back armrests, quick release rear wheels, 2 pt belt, heel loops, antitippers	Quick Release rear wheels. Optional offset frame to allow for AFOs	Handrims, Quick Release rear wheels, Footrest protector	Depth adjustable, stroller handle, folding backrest, interfaces with Leckey Squiggles and MyGo seats	Depth adjustable, stroller handle, folding backrest, interfaces with Leckey Squiggles and MyGo seats	Tilt mechanism, flipup spring-loaded anti tips, roller bearings for smooth tilt	Fixed frame. Adjustable seat depth, back height and width. Robust one piece footplate. Optional mud crusier front wheel	Fixed frame. Adjustable seat depth, back height and width. Robust one piece footplate. Optional mud crusier front wheel
BRAND	Karma	Ki Mobility	Ki Mobility	Ki Mobility	Ki Mobility	Ki Mobility	Ottobock	Ottobock

Information correct as of October 2024. From time to time, product specifications are changed by manufacturers without prior notice.



Paediatric Powerchair and Seating Solutions Chart

	POWERCHAIRS		
	PRIDE J623 2.0	EDGE 3 STRETTO	OTTOBOCK SKIPPI
DESCRIPTION	Excellent performance and outstanding stability. Ideal for kids who use a joystick to drive.	Our narrowest powerchair. Small footprint and tight turning radius make it ideal for kids and young adults. SRS suspension, and expandable Q-Logic 3 electronics.	Paediatric rear-wheel-drive powerchair for active users. Built in width and depth growth. Simple and transportable.
TYPE	Mid-Wheel-Drive	Mid-Wheel-Drive	Rear-Wheel-Drive
SEAT WIDTH RANGE	12" - 22"	12" - 20"	11.8" - 16.5"
SEAT DEPTH RANGE	12" - 22"	12" - 20"	11.4" - 14.6"
FOLDING	No	No	Can be dismantled
TILT 'N' SPACE	Optional 50°	Optional 50°	Yes, 25°
RECLINE RANGE	Optional	Optional	Manual, powered
MIN. SEAT-TO-FLOOR HEIGHT	17.5" with tilt	17.5" with tilt	17.5"
ADJUSTABLE HEIGHT PUSHCANES	Fixed Height Adjustable	Fixed Height Adjustable	Yes
GROWTH KIT INCLUDED	Built-in	Built-in	Built-in
STANDARD BRAKE	Electro-magnetic	Electro-magnetic	Electro-magnetic
USER WEIGHT LIMIT	136 kg	136 kg	50 kg
STANDARD FEATURES	Mid wheel 6 base, compatible with TRU-balance 3 power positioning, standard with ATX suspension, 4-pole motors	Independent Smooth Ride Suspension (SRS), Fender lights and USB charger. Q-Logic 3 expandable electronics. TRU-Balance 3 (or TB4 available on 16"x14" seat size and up)	Swingaway joystick, angle and height adjustable push handles, 12" drive wheels
BRAND	Pride	Quantum	Ottobock



Information correct as of October 2024. From time to time, product specifications are changed by manufacturers without prior notice.

