

Ki Mobility Liberty FT Express Script



Customer Details				
Client				
Assessor				
Organisation				
ACC		DSS		Other
User Weight				

Ki Mobility Liberty FT Express Script

If you only require specifications that fall under the Standard Express Package, you do not need to fill in the reverse page.

Choose either A or B		Seat Width			
		14"	16"	18"	20"
A	14"	☐ (.ULLIB141415FP1415)	☐ (.ULLIB161415FP1617)	☐ (.ULLIB181415FP1822)	☐ < 56kg ☐ 56 - 68kg ☐ 68 - 79kg
	15"	☐ (.ULLIB141415FP1415)	☐ (.ULLIB161415FP1617)	☐ (.ULLIB181415FP1822)	
	16"	☐ (.ULLIB1416FP1415)	☐ (.ULLIB1616FP1617)	☐ (.ULLIB1816FP1822)	
B	18"	☐ 68 - 79kg	☐ (.ULLIB161819FP1617)	☐ (.ULLIB181819FP1822)	☐ (.ULLIB201819FP1822)
	19"	☐ 79 - 90kg	☐ (.ULLIB161819FP1617)	☐ (.ULLIB181819FP1822)	☐ (.ULLIB201819FP1822)
	20"	☐ > 90kg	☐ (.ULLIB1620FP1617)	☐ (.ULLIB1820FP1822)	☐ (.ULLIB2020FP1822)

Code for all Express Packages is

KILIB14181416STDRED

KILIB16201820STDNAVY

Please enter code in brackets as well as the Standard Express Package code, above.

- A User Weight Range < 80kg
- B User Weight Range 68-90+kg

- A 16W needs Back Upholstery (KI004523)
- AB 18W needs Back Upholstery (KI004525)
- B 20W needs Back Upholstery (KI004527)

Express Package: (Select optional specifications and alternatives on reverse)

- Standard seat sling
- Transit tie downs
- Height adjustable straight back cane with push handle
- Fold down back (angle adjustable)
- Standard back upholstery
- 80° legrest hanger / front frame bend
- Aluminium angle adjustable footplates
- Long extension tube hangers
- 4-Way in line hanger release
- 6" castors - 1.5" soft roll aluminium
- 24in Spoke Performance Pneumatic Black Wheels
- Push to lock wheel locks
- Aluminium anodised handrims
- Quick release axles
- Height adjustable T-arm armrests with full arm pads
- Rear anti-tips
- Iridescent Navy Frame

Please note: Express Package includes some upcharge products.

Choose Your Specifications (No additional codes are required on the below parts)

Backrest Height				Seat to Footrest Length			
☐ 16"	☐ 17"	☐ 18"	☐ 19"	☐ 14"	☐ 15.5"	☐ 15"	☐ 15.5"
☐ 20"				☐ 16.5"	☐ 17"	☐ 17.5"	☐ 18"

Front Seat Height			
A	☐ 16"	☐ 16.5"	☐ 17"
B	☐ 17"	☐ 17.5"	☐ 18"

Optional Specifications			
Back Upholstery		1	
☐ Omit back upholstery			
Leg Hanger / Font Frame Bend		2	
☐ 70° (.ULLIBLEG70NAVY)		☐ Omit Hanger	
Medium (please specify):			
☐ 11.5" ☐ 12" ☐ 12.5" ☐ 13" ☐ 13.5"			
70° (.ULEXPSTF70M) 80° (.ULEXPSTF80M)			
Front Seat Height with 8 x 1" Poly + 7" Forks		3	
.ULLIBFSH21 (for 14" to 18" deep)			
.ULLIBFSH1920 (for 19" to 20" deep)			
☐ 18.5" ☐ 19" ☐ 19.5" ☐ 20"			
Armpad		4	
☐ Desk arm pad (.ULEXPAPD)			
Adjustable Heel Loops		5	
☐ 14-15W (.ULLIBHL1415)			
☐ 16-22W (.ULLIBHL1622)			
Calf Strap		6	
Velcro adjustable			
☐ 15-17W (.ULLIBCSVA1517)			
☐ 18-22W (.ULLIBCSVA1822)			
Padded velcro adjustable			
☐ 15-17W (.ULLIBCSPPVA1517)			
☐ 18-22W (.ULLIBCSPPVA1822)			
Notes			
Bodypoint padded aeromesh			
☐ 15-17W (.ULLIBCSAM1517)			
☐ 18-22W (.ULLIBCSAM1822)			
Wheel Lock Options (Only on Std. Push to lock)		7	
☐ Extension handles (.ULEXPWLKEXT)			
Push Rim Options - Standard Wheels		8	
☐ Plastic coated push rim (KI112821)			
☐ Ergonomic Standard Handrim - omit thumb grip (KI113083)			
☐ Thumb grip regular (KI100795)			
Rear Wheel Transit Kit		9	
☐ Rear wheel transit kit (.ULLIBWHL02)			
Includes the following: • 16" Mag wheel • Street Pneumatic			
Rear Wheel Kit - Low profile tyres		10	
☐ 24" Spoke Low Profile Schwalbe Marathon Plus natural fit LT omit thumb grip (KI119391)			
☐ Plastic coated push rim (KI112821)			
☐ Std aluminum push rim (KI200349)			
☐ Thumb grip regular (KI100795)			
☐ Ergonomic Standard Handrim - omit thumb grip (KI113083)			
PRO Elevated Legrest - Angle Adj. FP Long		11	
☐ 16/17 LHS (504526)		☐ 16/17 RHS (504534)	
☐ 18-25 LHS (504527)		☐ 18-25 RHS (504543)	
Residual Limb Support		12	
5" x 8" with smooth cover			
☐ Left (KI502355)		☐ Right (KI502354)	
7" x 10" with smooth cover			
☐ Left (KI502357)		☐ Right (KI502356)	
Accessories		13	
☐ Composite side guards (not used with armrests) (.ULLIBSDGC)			
☐ Black neoprene impact guards (.ULLIBIMG)			
☐ Clear spoke guards (.ULLIBSPGCL24)			
☐ Tray			

Notes