

204 KG WEIGHT CAPACITY



**Q6 Edge® HD**  
Shown with TRU-Balance® 3 HD  
Power Positioning and Q-Logic 3  
Drive Controls

## Q6 edge<sup>®</sup> HD

With features like standard 4-pole motors, Mid-Wheel 6<sup>®</sup> Drive Design and ATX Suspension, the Q6 Edge<sup>®</sup> HD is engineered to meet the performance needs of the most active user.

The Q6 Edge HD accepts a complete range of seating and electronics options to deliver exceptional rehab capability at an excellent value.

## Specifications

<b>DRIVE WHEELS</b>	35.56 cm (14")
<b>CASTERS</b>	<b>Front:</b> 15.24 cm (6") <b>Rear:</b> 15.24 cm (6")
<b>SUSPENSION</b>	ATX Suspension (Active-Trac® with extra stability) with enhanced rear suspension
<b>MAXIMUM SPEED</b> <sup>1</sup>	Up to 7.6 km/h (4.7 mph)
<b>BRAKES</b>	Intelligent braking (electronic, regenerative disc brakes)
<b>GROUND CLEARANCE</b> <sup>2</sup>	7.62 cm (3") at base frame
<b>TURNING RADIUS</b>	50.2 cm (19.75")
<b>OVERALL SIZE</b> <sup>2</sup> (Without Foot Riggings)	<b>Length:</b> 90.4 cm (35.6") <b>Width:</b> 66.68 cm (26.25")
<b>SEATING</b>	<p><b>Synergy® Seat</b> Adjustable Width: 51 cm - 71 cm (20"-28") Adjustable Depth: 51 cm - 71 cm (20"-28")</p> <p><b>TRU-Balance® 2 HD Power Positioning</b> Adjustable Width: 51 cm - 71 cm (20"-28") Adjustable Depth: 51 cm - 71 cm (20"-28")</p> <p><b>TRU-Balance® 3 HD Power Positioning</b> Adjustable Width: 51 cm - 71 cm (20"-28") Adjustable Depth: 51 cm - 63.5 cm (20"-25")</p> <p><b>High-back Seat</b> Width/Depth: 51 cm - 71 cm (20"-28")</p> <p><b>Medium-back Seat</b> Width/Depth: 51 cm - 71 cm (20"-28")</p>
<b>DRIVETRAIN</b>	Mid-Wheel 6®, 4-pole
<b>BATTERIES</b>	70 AH (Group 24)
<b>RANGE PER CHARGE</b> <sup>1,3</sup>	Up to 25 km (15.5 miles)
<b>BATTERY CHARGER</b>	8A, off-board
<b>AVAILABLE ELECTRONICS</b>	100A Q-Logic Drive Control System
<b>WEIGHT CAPACITY</b>	204 kg (450 lbs.)
<b>BASE WEIGHT</b>	65 kg (143.5 lbs.) (without batteries)
<b>BATTERY WEIGHT</b> <sup>4</sup>	23.6 kg (52 lbs.) (each)

- 1) Range and speed vary with user weight, terrain type, battery charge, battery condition and tyre pressure.
- 2) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.
- 3) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4, standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.
- 4) Battery weight may vary based on manufacturer.
- 5) Limited to 24" W x 24" D.

## Features

- Mid-Wheel 6® allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance® 3 HD Power Positioning
- Low impact OMNI-Casters (nylon, spherical-shaped castors) on front and rear prevent wheel hang-ups
- ATX Suspension (Active-Trac® with extra stability) incorporates front OMNI-Casters and semi-independent rear castor beam for enhanced performance over more varied terrain

## Options

- TRU-Balance® 3 (450 lbs.) HD Tilt, HD Recline, and HD Tilt & Recline
- Headrest
- Occupied transit for TRU-Balance® 2 HD Tilt<sup>5</sup>
- Occupied transit for Synergy® Seating<sup>5</sup>

## Colours



Red  
Corvette



Lime  
Light



Electric  
Blue



Deep  
Purple



Midnight  
Blue



Back  
in Black

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.



PO Box 302 250  
North Harbour  
Auckland, New Zealand

0800 31 61 81  
Ph: +64 9 415 1685  
Fax: +64 9 415 1686  
www.alliedmedical.co.nz



**ALLIED  
MEDICAL**  
L I M I T E D